



Hexagon Pillow (D-040)



Fabric requirements



Fabric A: 2241503 #3
Fat Eighth



Fabric B: 2241501 #2
Fat Eighth



Fabric C: 2142503 #1
Fat Eighth



Fabric D: 2241506 #1
Fat Eighth



Fabric E: 2241503 #2
Fat Eighth



Fabric F: 2241505 #1
Fat Eighth



Fabric H:
2241501 #1
Fat Quarter



Fabric J (Back Panels):
2241506 #3
1/2 yard




Fabric I (Binding):
2241504 #2
1/4 yard

Exclusive Pillow Design by Josée Carrier of The Charming Needle for Camelot Fabrics.
Fabric collection: Do What you Love by Alisse Courter from Camelot Fabrics



Fabric K
(Backing for quilted pillow front):
214-0001 White
2/3 yard



Fabric G:
214-0001 White
Fat Quarter



Blog, Facebook, Twitter @CamelotFabrics
Pinterest, YouTube & Instagram @Camelot_Fabrics
camelotfabrics.com • camelotfabricsblog.com
Toll-Free: 1-800-361-4120 • 514-382-2400
info@camelotfabrics.com • www.camelotfabrics.com

Finished size: 19" x 19"
Skill Level: Beginner


OTHER TOOLS & SUPPLIES

- (1) 20" square pillow form
- 21" x 21" piece of low loft batting
- needle and coordinating thread
- sewing machine
- iron & pressing surface
- rotary cutter and mat
- fabric shears
- straight pins
- fabric marker
- straight edge ruler with 60° line

NOTES

- For best results, read through all instructions before starting.
- Please wash, dry & iron your fabrics before beginning, and trim selvages.
- Unless otherwise indicated, sew all seams with a 1/4" seam allowance.
- Press your seams open as you go.
- WOF = width of fabric.

CUTTING





Fabrics A - F


Cut (1) 8-1/2" x 7" rectangle from each Fabric A-F

To make the Triangles: (Note: diagram shown is for a right-handed person)

- Align the 60° line of your ruler with the bottom edge of the rectangle. Position the ruler so that its long edge is crossing the rectangle's bottom right corner and cut.
- Rotate the fabric and the ruler 180°.
- Align the 60° line of your ruler with the top edge of the rectangle. Position the ruler so that its long edge is crossing the rectangle's bottom edge where the first cut ended. Cut to create the triangle.



Fabrics G - H



G

Cut (1) 20" x 4" rectangle and (1) 14" x 6-3/4 " rectangle.


Subcut the 14" x 6-3/4 " rectangle to create the pieces for each side of the half-hexagon:

-Align the 60° line of your ruler with the bottom edge of the rectangle. Position the ruler so that its long edge is crossing the top of the rectangle at 7" from its right edge (i.e. at the center of the top edge). Cut to make the first piece.



H


-Rotate the fabric and the ruler 180° and align the 60° line of your ruler with the top edge of the rectangle. Position the ruler so that its long edge is crossing where the first cut ended. Cut to make the second piece.




Fabric J (Back Panels)
Cut (1) 20" x 11-1/2" rectangle.
Cut (1) 20" x 16-1/2" rectangle.



Fabric I (Binding)
Cut (3) 2-1/2" x WOF strips.




Fabric K (Backing for quilted Pillow Front)
Cut (1) 24" x 24" square.




PIECING THE PILLOW FRONT

1. Sew the Fabric A & B triangles along 1 edge, Right Sides Facing, as shown.




2. Sew the Fabric F triangle to the opposite side of the Fabric A triangle, as shown.



3. Sew (1) Fabric G polygon to each side of the triangles unit as shown.

Note: Line up the polygon along the triangle's edge so that it extends 1/4" off the top.




Consequently, the triangles's corner will protrude 1/4" off the bottom of the polygon.



4. Trim the pieced unit to 20" wide, taking care to keep the middle triangle centered. You can trim the "dog-eared" seam allowances as well.

5. Sew your 20" x 4" Fabric G rectangle to the top of the work as shown.

This completes the upper half-hexagon section of the pillow front.




6. Repeat Steps 1-5 to create the lower half-hexagon section, using triangles in Fabrics C, D, E and background pieces in Fabric H.

7. Sew the upper & lower half-hexagons together, Right Sides Facing, taking care to align your seams.

ASSEMBLY

Quilting the Pillow Front:


1. Layer your white Fabric K backing piece, quilt batting and pillow front, with the batting in the center and the fabrics' Right Sides facing out.
2. Baste & quilt as desired, and square up the pillow front.



Adding the Pillow Back:

3. Fold & press a 1/2" hem along (1) 20" edge of each Fabric J Backing piece. Fold a second time and press. Topstitch along the fold.

4. Place the pillow front on your work surface, Wrong Side facing up. Place the narrower of the two Fabric J pieces on top of it, as shown, Right Side facing up (Note: the hemmed edge should be towards the center).



5. Place the second Fabric J piece on the pillow front, as shown, Right Side facing up. Again, the hemmed edge is placed towards the center.

6. Pin and sew a seam around the perimeter of the pillow with 1/8" seam allowance.

7. Join the Fabric I binding strips and press to make the binding. Sew the binding to the pillow using your favorite method.